

## BR series 19" Wall-Mount Solution



For the environment where physical floor space is at premium, wall-mount rack is an excellent way to provide a flexible rackmount solution. The robust and cost efficient BR series wall-mount rack is ideal for telecom, academic retail, hospital, warehouse, and other applications with space limited areas.

### ISO-Certified

9001 14001

The design and manufacturing process of the series achieves the BSi ISO9001 quality control plus ISO14001 environment standard.

50 kg

110 lb

Designed for wall-mount application, the BR series rack holds 50 kg / 110 lb load rating.

## Key Benefits

### >>> Strong Construction

Fully welded construction for strength

### >>> Floor-Support Available

Optional casters available so that the wall-mount rack can be placed on floor.

### >>> Convenient Top / Bottom Cable Access

Enhance cabling and patch cord installation

### >>> Front Door with Tempered Glass

The fully enclosed rack provides protection from dust in crowd area. Glass door maximize viewing of equipment.

### >>> Reversible Hinged Door

User friendly design provides left / right door open flexibility

### >>> Lockable Door for Security

Front doors and side panels installed with mechanical locks for rack access security

### >>> Removable Front Door / Side Panels

Design for flexible and easier installation.

### >>> Optional Fan Kit Available

Promote proper cooling by fan kits and filters

### >>> Variety of Dimensions

Height range from 6U to 17U. Depth range from 500 mm to 600 mm.

### >>> Fully Assembled

On-site assembly is not required

## Standard Package / Size

	Model No.	Width		Depth		Height			
						Overall		Effective	
		mm	inch	mm	inch	mm	inch	mm	inch
6U	BR-6.5	600	24"	537	21"	343	14"	267	11"
	BR-6.6	600	24"	637	25"	343	14"	267	11"
9U	BR-9.5	600	24"	537	21"	477	19"	400	16"
	BR-9.6	600	24"	637	25"	477	19"	400	16"
12U	BR-12.5	600	24"	537	21"	610	24"	533	21"
	BR-12.6	600	24"	637	25"	610	24"	533	21"
15U	BR-15.5	600	24"	537	21"	743	29"	667	26"
	BR-15.6	600	24"	637	25"	743	29"	667	26"
17U	BR-17.5	600	24"	537	21"	832	33"	756	30"
	BR-17.6	600	24"	637	25"	832	33"	756	30"

\*\*Custom size on request



### Configuration

Static Loading: 50 kg / 110 lb

Color : Grey White

Main Framework

Vented Top Cover w/ Cable Access Channel

19" Rails, Front Pair

Front Glass Door w/ Lock

Detachable Steel Rear Panel


Side Panel w/ Lock, Pair

M6 Screw Fixing, Pack of 20

### Standard Color

- Grey White (RAL 9002)

\*\* Custom color on request



## Optional Accessories

### Cable Management

- CMP-1B** 1U cable management panel  
**CMP-2B** 2U cable management panel

### Cooling Fan Unit

- BR-F2** Top fan tray w/ 2 fans

### Shelf, 19" mounting

- MS19** Cantilever shelf, 190 mm deep, 20 kg loading  
**MS40** Cantilever shelf, 400 mm deep, 20 kg loading

### Caster

- MC** Lockable caster, set of 4

### Rackmount PDU

- H8UK90-13A\_BS/3B-1** Basic PDU, 8-way ( 1.25U )  
**H7UK90-13A\_BS/3B-1** Basic PDU, 7-way ( 1.25U )  
**H6UK90-13A\_BS/3B-1** Basic PDU, 6-way ( 1.25U )  
**H5UK90-13A\_BS/3B-1** Basic PDU, 5-way ( 1.25U )  
**H4UK90-13A\_BS/3B-1** Basic PDU, 4-way ( 1.25U )
- H7UK90-13A-MD\_BS/3B-1** Metered PDU, 7-way ( 1.25U )  
**H6UK90-13A-MD\_BS/3B-1** Metered PDU, 6-way ( 1.25U )  
**H5UK90-13A-MD\_BS/3B-1** Metered PDU, 5-way ( 1.25U )  
**H4UK90-13A-MD\_BS/3B-1** Metered PDU, 4-way ( 1.25U )

\* IEC C13 / C19 outlet available